

AUSTONE TIRES



AAR602



Toda posición

MEDIDA	CAPAS	ÍNDICE DE CARGA	ÍNDICE DE VELOCIDAD	PROFUNDIDAD	ANCHO DE RIN	CAPACIDAD DE CARGA (Kg)	PRESIÓN (PSI)
11R22.5	16PR	146/143	L	14.5	8.25	3000/2725	120
11R22.5	18PR	149/146	L	14.5	8.25	3250/3000	135
11R24.5	16PR	149/146	L	14.5	8.25	3250/3000	120
215/75R17.5	16PR	135/133	L	12	6	2180/2060	125
225/70R19.5	14PR	128/126	L	12	6.75	1800/1700	110
245/70R19.5	16PR	135/133	L	13.5	7.5	2060/1950	110
245/70R19.5	16PR	135/133	L	13.5	7.5	2240/2120	120
285/75R24.5	16PR	147/144	L	14.5	8.25	3075/2800	120
295/75R22.5	16PR	146/143	L	14.5	9	3000/2725	120



AAR603



Toda posición

MEDIDA	CAPAS	ÍNDICE DE CARGA	ÍNDICE DE VELOCIDAD	PROFUNDIDAD	ANCHO DE RIN	CAPACIDAD DE CARGA (Kg)	PRESIÓN (PSI)
235/75R17.5	18PR	143/141	J	13	6.75	2725/2575	125
255/70R22.5	16PR	140/137	M	14	7.5	2500/230	120
275/70R22.5	18PR	146/143	M	15	8.25	3000/2725	130




AT116A



Toda posición

MEDIDA	CAPAS	ÍNDICE DE CARGA	ÍNDICE DE VELOCIDAD	PROFUNDIDAD	ANCHO DE RIN	CAPACIDAD DE CARGA (Kg)	PRESIÓN (PSI)
11R22.5	16PR	148/145	M	15	8.25	3150/2900	125
295/80R22.5	18PR	152/149	M	16	9	3550/3250	130
315/80R22.5	20PR	157/154	L	16	9	4125/3750	130




ADH106



Tracción

MEDIDA	CAPAS	ÍNDICE DE CARGA	ÍNDICE DE VELOCIDAD	PROFUNDIDAD	ANCHO DE RIN	CAPACIDAD DE CARGA (Kg)	PRESIÓN (PSI)
11R22.5	16PR	146/143	L	24	8.25	3000/2725	120
11R22.5	18PR	149/146	L				
11R24.5	16PR	149/146	L	24	8.25	3250/3000	120
11R24.5	18PR	149/146	L				
295/75R22.5	16PR	146/143	L	24	9	3000/2725	120



AT125



Tracción

MEDIDA	CAPAS	ÍNDICE DE CARGA	ÍNDICE DE VELOCIDAD	PROFUNDIDAD	ANCHO DE RIN	CAPACIDAD DE CARGA (Kg)	PRESIÓN (PSI)
11R22.5	16PR	148/145	L	21.5	8.25	3150/2900	125
11R22.5	18PR	149/146	L	21	8.25	3250/3000	135
11R24.5	16PR	149/146	L	21.5	8.25	3250/3000	120



AAM211



Servicio Mixto

MEDIDA	CAPAS	ÍNDICE DE CARGA	ÍNDICE DE VELOCIDAD	PROFUNDIDAD	ANCHO DE RIN	CAPACIDAD DE CARGA (Kg)	PRESIÓN (PSI)
425/65R22.5	20PR	165	K	18	12.25	5150	120



AT326A



Minera

MEDIDA	CAPAS	ÍNDICE DE CARGA	ÍNDICE DE VELOCIDAD	PROFUNDIDAD	ANCHO DE RIN	CAPACIDAD DE CARGA (Kg)	PRESIÓN (PSI)
11R22.5	16PR	146/143	J	18	8.25	3000/2725	120